

REMO Removable Safety-Grip™ Data Sheet

| Subject | Result | Test Method |
|---------------------------------|---------------------------|-----------------|
| Back carrier | 0.004in PVC + 0.004in PET | Caliper method |
| Type of adhesive | Solvent acrylic | N/A |
| Mineral type | Aluminium Oxide | N/A |
| Adhesion to steel (psi) | 16.8↑ | PSTC-4 |
| Temperature range | 23°F to +122°F | See notes below |
| Maximum size of production roll | 46 x 328ft | N/A |
| Resistance to water | Good | PSTC-35 |
| Life (months) | 12 to 24 | PSTC-9 |

LRV Test Results

| SKU (Color) | RAL | Pantone | Av. LRV | Range |
|----------------------------------|-------------|---------------|------------|-------|
| REMO_N (Black) | 9004 | Black U | 0.3 | 0.1 |
| REMO_Y (Yellow) | 1003 | 115 U | 48.4 | 1.4 |
| REMO_D (Black/ Yellow Hazard) | 9004 / 1003 | Black / 112 U | 0.7 / 81.5 | 2 / 3 |

The independent test laboratory at Adhesive Technical Services Ltd performed the temperature test, England (test results available)

The above tests were conducted in accordance with Pendulum, the tests were conducted at a recognized independent friction testing laboratory, and copy certificates are available on request. Pendulum is a dynamic test, for static tests, we also have results ASTM C 1028-96.

All the above data is for reference only.

©Heskins Ltd 1997-2024