

NSTT Thick Safety-Grip™ Data Sheet

Subject	Result	Test Method
Back carrier	0.08in PVC	Caliper method
Type of adhesive	Solvent acrylic	N/A
Total thickness	0.084in	Caliper method
Mineral type	Aluminium Oxide	N/A
Adhesion to steel (psi)	84↑	PSTC-4
Temperature range	-22°F to +158°F	See notes below
Maximum size of production roll	46in x 164ft	N/A
Resistance to water (months)	10	PSTC-35
Resistance to chemicals (months)	8	PSTC-35
Resistance to motor oil	Excellent	PSTC-35
Life (months)	12 to 24	PSTC-9

LRV Test Results

SKU (Color)	RAL	Pantone	Av. LRV	Range
NSST_N (Black)	9004	Black U	0	0
NSST_Y (Yellow)	1003	109 U	39.7	2.12

Coefficient of Friction Data

Test	Dry Surface Test Result	Wet Surface Test Result	Test Standard
Pendulum	102 TRL	71 TRL	EN 13036-4
DIN51130	R13		Certificate UK23247-1817
DIN51097	Inclination 30°- C		97910801.004
NFSI	High traction		Expiry: 20/12/2025

The above tests were conducted in accordance with Pendulum, the tests were conducted at a recognized independent friction testing laboratory, and copy certificates are available on request. Pendulum is a dynamic test, for static tests, we also have results ASTM C 1028-96.

All the above data is for reference only.

©Heskins LLC